



PARAMOUNT READY-MIX CONCRETE, INC.
Los Angeles & Orange County
 P.O. Box 2823
 13949 E. Stage Road, Santa Fe Springs CA 90670
 (562) 404-4125 - Fax (562) 802-3792

CON-PUMP COMPANY, INC.
 P.O. Box 2823
 Santa Fe Springs, CA 90670
 (562) 404-3729

MATERIAL SAFETY DATA SHEET

SECTION I

MANUFACTURERS NAME AND ADDRESS

PARAMOUNT READY MIX CONCRETE, INC.
 13949 E. STAGE ROAD
 P.O. BOX 2823
 SANTA FE SPRINGS, CA 90670

EMERGENCY TELEPHONE #

(562) 404-4125 EXT. 1

PRODUCT NAME

PORTLAND CEMENT CONCRETE -- PLASTIC (UNHARDENED)

SECTION II

HAZARDOUS INGREDIENTS

PORTLAND CEMENT CONCRETE CONTAINS PORTLAND CEMENT, WHICH IS CLASSIFIED AS A NUISANCE DUST, AND ALTHOUGH IT IS NOT LISTED AS CONTAINING CARCINOGENS, IT DOES CONTAIN CHEMICALS KNOWN TO CAUSE CANCER, BIRTH DEFECTS AND OTHER REPRODUCTIVE HARM. PORTLAND CEMENT CONCRETE ALSO CONTAINS OTHER DETECTABLE CHEMICAL COMPOUNDS WHICH MAY BE CONSIDERED HAZARDOUS.

SECTION III

PHYSICAL CHARACTERISTICS

BOILING POINT	N/A	VAPOR PRESSURE	N/A
VAPOR DENSITY	N/A	SPECIFIC GRAVITY	2.37
PERCENT VOLATILITY	N/A	APPEARANCE/ODOR	GRAY/NONE
SOLUBILITY IN WATER	N/A	EVAPORATION RATE	LESS THAN .8LBS/ SQ.FT.>HR.

SECTION IV

FIRE AND EXPLOSION HAZARD DATA

FLASH POINT	N/A	SPECIAL FIRE FIGHTING PROCEDURES	N/A
EXTINGUISHING MEDIA	N/A	UNUSUAL FIRE/EXPLOSION HAZARDS	N/A
FLAMMABLE/EXPLOSIVE LIMIT	N/A		

SECTION V

REACTIVITY DATA

STABILITY	PRODUCT IS STABLE
INCOMPATIBILITY	N/A
HAZARDOUS DECOMPOSITION PRODUCTS	NONE.
HAZARDOUS POLYMERIZATION	WILL NOT OCCUR.

SECTION VI

HEALTH HAZARD DATA

EMERGENCY AND FIRST AID PROCEDURES	IRRIGATE EYES WITH WATER, CONSULT A PHYSICIAN IMMEDIATELY. WASH EXPOSED AREAS WITH SOAP AND WATER.
EFFECTS OF OVERDOSE	PLASTIC (UNHARDENED) CONCRETE CAN DRY THE SKIN AND CAUSE ALKALI BURNS.

SECTION VII

PRECAUTIONS FOR SAFE HANDLING

CLEAN-UP PROCEDURE	ALLOW CONCRETE TO HARDEN AND REMOVE. TREAT AS NORMAL WASTE.
WASTE DISPOSAL METHOD	MATERIAL CAN BE RETURNED TO BATCH PLANT, OR ALLOWED TO HARDEN AND DISPOSED OF AS NORMAL WASTE.

SECTION VIII

SPECIAL PROTECTION INFORMATION

SKIN PROTECTION	USE BARRIER CREAMS, GLOVES, BOOTS AND CLOTHING TO PROTECT THE SKIN FROM PROLONGED CONTACT WITH PLASTIC CONCRETE. IMMEDIATELY AFTER WORKING WITH PLASTIC CONCRETE, WORKERS SHOULD SHOWER WITH SOAP AND WATER. PRECAUTIONS MUST BE OBSERVED, BECAUSE CONCRETE/ALKALI BURNS WITH LITTLE WARNING. A SLIGHT SENSATION OF HEAT CAN BE SENSED.
EYE PROTECTION	THE USE OF TIGHT FITTING GOGGLES IS RECOMMENDED.
